Cambridge Brass P.O. Box 249 140 Orion Place 140 Onon Place Cambridge, Ontario Canada N1R 5V1 Tel: (519) 621-5520 Fax: (519) 621-8674 http://www.cambridgebrass.com






MODEL NO. 105NL

CB COMPRESSION x CB COMPRESSION

FIL COUPLING

## CB COMPRESSION FOR COPPER OR PLASTIC TUBING (CTS)



- PARTS AND MATERIAL:
  1. ELBOW BODY: CAST BRASS, ALLOY C89833
  2. CONDUCTOR SPRING: BRASS
  3. COMPRESSION NUT: CAST BRASS, ALLOY C83600
  4. COMPRESSION SEAL: EPDM
  5. GRIPPER: STAINLESS STEEL, ALLOY 302

## **FEATURES:**

- ALL COMPONENTS CONFORM TO AWWA C800
  (ASTM B-584 UNS NO C89833 FOR BRASS PARTS IN CONTACT WITH POTABLE WATER,
- AND ASTM B-62 AND B-584 UNS NO C83600 FOR ALL OTHER BRASS PARTS).

   CONFORMS TO ANSI/NSF 61-8

   CONFORMS TO ANSI/NSF 372 (COMPLIANT WITH US Safe Drinking Water Act. PL 111 - 380)
- 300 PSI WORKING PRESSURE

Cambridge Brass considers the information in this submittal form to be correct at the time of publication. Item and option availability, including specifications, are subject to change without notice.

ELL COUPLING SIZE	CATALOG NO.	CB COMPRESSION BOTH ENDS	LENGTH	HEIGHT	APPROX. WT. LBS.
3/4"	105NL-H3H3	3/4"	1.50"	1.50"	1.1
1"	105NL-H4H4	1"	1.79"	1.79"	2.0
1 1/2"	105NL-H6H6	1 1/2"	2.60"	2.60"	4.1
2"	105NL-H7H7	2"	3.14"	3.14"	6.0

Submitted by: