
Cambridge Brass P.D. Box 249 140 Orion Place Cambridge, Ontario Canada N1R 5V1 Tel: (519) 621-5520 Fax: (519) 621-8674 http://www.cambridgebrass.com





MODEL NO. 210NL

GRIP JOINT X METER YOKE NOSE

ANGLE YOKE STYLE BALL VALVE FULL PORT WITH LOCKWING


FOR COPPER OR PLASTIC TUBING (CTS) x METER YOKE NOSE

PARTS AND MATERIAL:

- 1. VALVE BODY: CAST BRASS, ALLOY C89833
 2. LOCKING CAP: CAST BRASS, ALLOY C83600
 3. CAP SCREW: STAINLESS STEEL, TYPE 304
 4. STEM: STAINLESS STEEL, TYPE 303
 5. O-RING: NITRILE RUBBER

- 5. O-RING: NIRILE RUBBER
 6. ENDBODY: CAST BRASS, ALLOY C89833
 7. SEATS: TEFLON
 8. BALL: CAST BRASS, ALLOY C89833
 9. GRIP JOINT NUT: CAST BRASS, ALLOY C83600
 10. GASKET: NITRILE RUBBER
 11. GRIPPER: BRASS, ALLOY C26000
 12. WASHER: POLYETHENE
 13. STAP JULY: CAST BRASS, ALLOY C83600

- 13. STAR NUT: CAST BRASS, ALLOY C83600



- FEATURES:
 MANUFACTURED IN COMPLIANCE WITH AWWA STANDARD C800-05 (ASTM B-584 UNS NO C89833 FOR BRASS PARTS IN CONTACT WITH POTABLE WATER,
- AND ASTM B—62 AND B—584 UNS NO C83600 FOR ALL OTHER BRASS PARTS).

 CONFORMS TO ANSI/NSF 61—8

 CONFORMS TO ANSI/NSF 372 (COMPLIANT WITH US Safe Drinking Water Act. PL 111—380)

 FLOW CAN BE IN EITHER DIRECTION.

 ROTATION STOPS RESISTS 200 FT—LB TORQUE.

 ENCAPSULATED LUGS UNDER CAP PROVIDE 90 DEGREE OPEN TO CLOSE OPERATION.

- BLOWOUT PROOF DESIGN.
 300 PSI WORKING PRESSURE.
- HOLE FOR ATTACHING HANDLE IS PROVIDED IN CAP. PADLOCK WING FOR LOCKING BALL IN CLOSED POSITION.

ORDERING INFORMATION:

FULL 360 ROTATION = ADD "R" TO END OF CATALOG NO.
HANDLE = ADD "H" TO END OF CATALOG NO. AND ADD 0.75" HEIGHT TO DIM. A
TALL CAP = ADD "P" TO END OF CATALOG NO. AND ADD 0.58" HEIGHT TO DIM. A

Cambridge Brass considers the information in this submittal form to be correct at the time of publication. Item and option availability, including specifications, are subject to change without notice.

VALVE SIZE	CATALOG NO.	GRIP JOINT	METER SIZE	HEIGHT	LENGTH	"A"	APPROX. WT. LBS.
3/4"	210NL-GJ3SR1	3/4"	5/8"	1.53"	2.25"	1.92"	
3/4"	210NL-GJ3SR3	3/4"	5/8"x3/4" & 3/4"	1.53"	2.25"	1.92"	
1"	210NL-GJ4SR3	1"	5/8"x3/4" & 3/4"	1.84"	2.08"	2.10"	
1"	210NL-GJ4SR4	1"	1"	1.84"	2.53"	2.10"	

Submitted by: