


NEW

TECK™ 403 Series

Stainless-Steel Termination Sleeve for 6" Diameter

8600 Series Two Piece Stainless-Steel

The TECK™ stainless steel termination sleeves are used to seal off and protect decommissioned corporation stops, in direct tap applications. TECK™ termination sleeves feature chemically passivated welds, Teflon coated nuts & NBR gasket. Currently available for 6" diameter pipe that terminates valves from 1/2" to 1", with additional sizes to be offered shortly. Installation instructions are provided with each termination sleeve. Please read and follow instructions to ensure long lasting performance.

Features:

- All Sleeve components made of 18-8 type 304 stainless-steel
- Fully passivated for corrosion resistance
- Recommend sleeve bolt torque is 80 FT/LBS
- Conforms to ANSI/NSF Standard 61-8
- Rated for 250 PSI working pressure

Materials:

- Sleeve Body - 18-8 Type 304 stainless-steel
- Sleeve Waffle Gasket - NBR, meets NSF 61
- Sleeve Ring Gasket - NBR, meets NSF 61
- Bolts - 18-8 Type 304 stainless-steel, 5/8" Roll NC thread
- Nuts - 5/8-11 thread, Type 304 stainless-steel, heavy hex, Teflon coated to prevent galling
- Washers - 18-8 Type 304 stainless-steel
- Integrated dual bridge plates - 18-8 Type 304 stainless-steel



| Nom. O.D. | O.D. Pipe | O.D. Range | Sleeve Width | Terminates Valves | Outlet Size Code | Part Number |
|-----------|-----------|-------------|--------------|-------------------|------------------|---------------|
| 6 | 6.90 | 6.50"-7.30" | 8" | 1/2" to 1" | 4 | 8600-0690-8-4 |